# WF Education Group - Safety Data Sheet

CY14005

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1 Revision date: 16 April 2021 Date printed: 07 June 2021

## **Section 1. Identification**

**1.1 Product Identifier** CY14005

Product Name CYCLOHEXANE pure 1L.

CAS Number 110-82-7

REACH Registration No 01-2119463273-41-XXXX

Molecular Formula

CH\_(CH\_2) CH\_ =84.16

### 1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

#### **1.3 Supplier** WF Education Group

VICKERS
Working together with
TIMSTAR
Part of Commedication Group

Phoenix House

Battlefield Enterprise Park

Stafford Drive Shrewsbury Shropshire SY1 3FE

UNITED KINGDOM

Phone +44(0)1743 812200 Email sales@wf-education.com Website www.timstar.co.uk

**1.4 Emergency Telephone** (08:30-17:00) +44(0)1743 812200

(24hr) 112

(Have this document to hand)

## Section 2. Hazards Identification

### 2.1 Classification of the substance or mixture

## Classification according to regulation 1272/2008/EC

Flammable liquid, category 2 Skin corrosion/irritation, category 2

Spec target organ tox - single, category 3

Aspiration hazard, category 1

Hazard to aquatic environment, category 1

Hazard to aquatic environment, category 1

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H304: May be fatal if swallowed and enters airways.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

### 2.2 Label elements

### Labelling according to regulation 1272/2008/EC

Signal word Danger

Hazard Pictograms









Hazard Statements Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May

cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects.

Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. Precautionary Statements

Avoid breathing dust / fume / gas / mist / vapours / spray. IF SWALLOWED: Immediately call a POISON

CENTER or doctor/physician. Do NOT induce vomiting.

## **Section 3. Composition**

#### 3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Cyclohexane	110-82-7	203-806-2	01-2119463273-41-XXXX	>99.5%	Flam. Liq. 2,Skin Irrit. 2,STOT SE 3 (D),Asp. Tox. 1,Aquatic Acute 1,Aquatic Chronic 1

## Section 4. First Aid

### 4.1 Description of first aid measures

Eves Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. If discomfort persists

OBTAIN MEDICAL ATTENTION.

Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use. Skin

OBTAIN MEDICAL ATTENTION.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery

position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

### **Section 5. Fire Fighting**

### 5.1 Extinguishing media

Extinguishing Media Alcohol resistant foam, dry powder, carbon dioxide or vaporising liquid. Use water spray to keep fire exposed

containers cool.

Unsuitable Media Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

#### 5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

## Section 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate

area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

### 6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Environmental Health Officer if major spillage occurs.

### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

#### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

## Section 7. Storage & Handling

#### 7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

#### 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

#### 7.3 Specific end use(s)

See section 1.2.

## Section 8. Workplace Exposure & Personal Protection

### 8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits					
			Long Term (8hr TWA)		Short Term 15min period)			
Cyclohexane	110-82-7	>99.5%	100.0 ppm	300.0 mg/m-3	350.0 ppm	1050.0 mg/m-3		

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

## Section 9. Physical & Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.
Odour Characteristic.
pH Not applicable
Boiling Point 80.7°C

Melting Point 6.5°C

Flash Point -18°C (Closed cup)

Upper Flammable Limit
Lower Flammable Limit
Auto Ignition

8%
1.3%
260°C

Explosive Properties Severe in confined spaces.

Oxidising Properties No.

Vapour Pressure 100mmHg @ 61°C

Relative Density 0.7800 Water Solubility 0.01%

#### 9.2 Other information

No data available.

## Section 10. Stability & Reactivity

**10.1** Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

**10.3** Possibility of hazardous

reactions

No data available.

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Strong oxidising agents. Inter halogen compounds eg.bromide tri and pentafluoride, iodine penta and

heptafluorides etc.

10.6 Hazardous Decomposition

**Products** 

None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

## Section 11. Toxicological Information

### 11.1 Information on toxicological effects

Eyes Both the vapour and liquid are, irritating to the eyes.

Skin Repeated or prolonged contact may defat the skin producing irritation and dermatitis.

LD50 Skin >2000mg/kg Rabbit

Ingestion May be fatal if swallowed and enters airways.

LD50 Oral >5000mg/kg Rat

Inhalation Exposure to vapour concentrations above the occupational exposure limits may produce irritation of the eyes and

respiratory tract. High concentrations of vapour will cause narcosis, anaesthesia and fatigue.

LD50 Inhalation 32880mg/m3 Rat (4 hours)

TCLo Not available

Carcinogenicity Not considered to be a carcinogen.

Mutagenicity Not considered to be a mutagen.

Reproductive Effects None identified.

### Section 12. Ecological

12.1 Toxicity Moderately toxic to mammals, fish and bacteria. Very Toxic to aquatic organisms and may cause long term

adverse effects in the aquatic environment.

LC50 Algal Not available

LC50 Crustacea 0.9mg/l Daphnia magna (48 hours)
LC50 Fish 4.53mg/l Fathead Minnow (96 hours)

**12.2** Persistence and No data available.

degradability

12.3 Bioaccumulative potential No data available.12.4 Mobility in soil No data available.

**12.5** Results of PBT & vPvB Assessment not required. assessment

**12.6** Other adverse effects None known at present.

# Section 13. Disposal Considerations

### 13.1 Waste treatment methods

Disposal Methods Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

## **Section 14. Transport Information**

**14.1 UN Number** 1145

14.2 Proper Shipping Name Cyclohexane

14.3 Transport classes

UN classification 3
Subsidiary hazard(s) None
Transport category 2
ADR Hazard ID 33
Tunnel Restriction Code D/E

14.4 Packing Group II

**14.5 Environment hazards** See section 12.

**14.6 Special precautions for** No special precautions required.

user

**14.7 Transport in bulk** Not transported in bulk.



15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 2; Skin corrosion/irritation, category 2; Spec target organ tox - single, category 3;

Aspiration hazard, category 1; Hazard to aquatic environment, category 1; Hazard to aquatic environment, category 1

Signal word Danger

Hazard Pictograms









Hazard Statements H225, H304, H315, H336, H410

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects.

Precautionary Statements P233, P280, P261, P301+P310, P331

Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. Avoid breathing dust / fume / gas / mist / vapours / spray. IF SWALLOWED: Immediately call a POISON

CENTER or doctor/physician. Do NOT induce vomiting.

### 15.2 Chemical safety assessment

Assessment not required.

### Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 07 June 2021

Copyright: 2021 WF Education Group