WF Education Group - Safety Data Sheet

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 1.1

Revision date: Date printed:

16 April 2021 07 June 2021

WA14005

Section 1. Identification

1.1	Product Identifier	WA14005
	Product Name	WANKLYN'S SOAP SOLUTION 1L.
	CAS Number REACH Registration No	Mixture A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.

1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier

WF Education Group

Phoenix House

Stafford Drive Shrewsbury

Shropshire SY1 3FE

Battlefield Enterprise Park

UNITED KINGDOM



Phone Email Website +44(0)1743 812200 sales@wf-education.com www.timstar.co.uk

1.4	Emergency Telephone	(08:30-17:00)	+44(0)1743 812200
		(24hr)	112
		(Have this doc	ument to hand)

Section 2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to regulation 1272/2008/EC

Flammable liquid, category 3 Serious eye damage/irritation, category 2 H226: Flammable liquid and vapour. H319: Causes serious eye irritation.

2.2 Label elements

Labelling according to regulation 1272/2008/EC

Signal word

Hazard Pictograms

Warning



Hazard Statements

Flammable liquid and vapour. Causes serious eye irritation.

Keep container tightly closed. Wear protective gloves / protective clothing / eye protection / face protection. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing.

Section 3. Composition

3.2 Mixtures

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Ethanol	64-17-5	200-578-6	01-2119457610-43-XXXX	57%	Flam. Liq. 2,Eye Irrit. 2
Methanol	67-56-1	200-659-6	01-2119433307-44-XXXX	1.5%	Flam. Liq. 2, Acute Tox. 3 (O), Acute Tox. 3 (D), Acute Tox. 3 (I), STOT SE 1
Potassium hydroxide	1310-58-3	215-181-3	01-2119487136-33-XXXX	0.2%	Met. Corr. 1,Skin Corr. 1A,Acute Tox. 4 (O)

Section 4. First Aid

4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

5.1 Extinguishing media

Extinguishing Media	Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
TT 1.11 N.C. 11	

Unsuitable Media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Vapour-air mixtures are explosive.

5.3 Advice for firefighters

Hazards

Advice for firefighters

Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.

6.2 Environmental precautions

Enviromental

Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits			
			Long Term (8h	r TWA)	Short Term 15mi	n period)
Ethanol	64-17-5	57%	1000.0 ppm	1920.0 mg/m-3	-	-
Methanol	67-56-1	1.5%	200.0 ppm	266.0 mg/m-3	250.0 ppm	333.0 mg/m-3
Potassium hydroxide	1310-58-3	0.2%	-	-	-	2.0 mg/m-3

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

Respiratory Protection	Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.
Hand Protection	Use solvent resistant gloves.
Eye Protection	Use tightly fitting chemical splash proof glasses or goggles.
Skin Protection	Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.
Special Hazards	No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance	Clear colourless to pale yellow liquid.
Odour	Fresh and characteristic.
pH	7 @ 20°C
Boiling Point	81°C
Melting Point	-42°C
Flash Point	22°C (Closed cup)
Upper Flammable Limit	19%
Lower Flammable Limit	3.3%
Auto Ignition	363°C
Explosive Properties	Moderate/severe in confined spaces.
Oxidising Properties	No.
Vapour Pressure	59mmHg @ 20°C

Ref: WA14005

Relative Density Water Solubility 0.9000 Completely miscible in water.

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1	Reactivity	No data available.
10.2	Chemical Stability	Stable under normal conditions
10.3	Possibility of hazardous reactions	No data available.
10.4	Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5	Incompatable Materials	Strong oxidising agents.
10.6	Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes	The liquid will cause conjunctival irritation and corneal damage. High concentrations of vapour may be irritating to the eyes.
Skin	Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Unlikely to be absorbed across the skin in harmful amounts.
LD50 Skin	Not available
Ingestion	Low order of acute toxicity. Fatal dose in man 300-400ml. Ingestion of large amounts will produce central nervous system depression. Symptoms may include nausea, vomiting muscular incoordination and loss of consciousness. Aspiration during swallowing or vomiting may injure lungs.
LD50 Oral	Not available
Inhalation	Exposure to vapour concentrations above the occupational exposure limits may produce irritation of the eyes and respiratory tract. High concentrations of vapour may produce central nervous system depression and unconsciousness. Symptoms will be similar to those following ingestion.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	Some evidence for foetoxicity and tetragenecity has been observed in experimental animals treated with high doses of ethanol during gestation.
Other Information	Contains methanol. This will not constitute a special problem since ethanol is preferentially metabolised. Chronic intoxication may however produce damage to the optic nerve.

Section 12. Ecological

12.1	Toxicity	Ethanol is readily biodegradable after 15 days in non-acclimated fresh water. 75% biodegradability occurs after 20 days in salt water.
	LC50 Algal	Not available
	LC50 Crustacea	Not available
	LC50 Fish	Not available
12.2	Persistence and degradability	No data available.
12.3	Bioaccumulative potential	No data available.
12.4	Mobility in soil	No data available.
12.5	Results of PBT & vPvB assessment	Assessment not required.
12.6	Other adverse effects	None known at present.

WF Education Group - Safety Data Sheet

Ref: WA14005

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods

Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1	UN Number	1170	•
14.2	Proper Shipping Name	Ethanol	, the
14.3	Transport classes UN classification Subsidiary hazard(s) Transport category ADR Hazard ID Tunnel Restriction Code	3 None 2 33 D/E	FLAMMABLE LIQUID
14.4	Packing Group	П	
14.5	Environment hazards	See section 12.	
14.6	Special precautions for user	No special precautions required.	
14.7	Transport in bulk	Not transported in bulk.	

Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)ClassificationFlammable liquid, category 3; Serious eye damage/irritation, category 2Signal wordWarningHazard PictogramsImage: Colspan="2">Image: Colspan="2">Colspan="2"Colspa

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supercedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 07 June 2021

Copyright: 2021 WF Education Group